

# RANGE G

## PALLETS & ACCUMULATION CENTERS FOR SPILL CONTAINMENT



### CERTIFICATION

- In compliance with EPA, SPCC, UL Environment, NFPA1 and OSHA (see models) specifications.

### ADVANTAGES

- High chemical resistance
- Easy cleaner.

### TECHNICAL SPECIFICATION

- Built in 100% recycled polyethylene.
- Removable grating built in 100 % recycled polyethylene.
- From 2 to 8 drums of 60, 100 ou 200 litres storage.
- Wide forklift pockets facilitate relocation (only for 28234 and 28254 models).

### OPTIONS

- Companion ramp for accumulation center 28923 and AK28905 (Réf.: AK28906).
- Joining clips to connect 2 accumulation centers 28923 and AK28905 (Réf.: 28926).
- Industrial absorbing mat (P/N : JF10D).

P/N	Description	Dimensions H x W x D (mm)	Load bearing capacity (kg)	Containment capacity (L)	Conformity <sup>(1)</sup>	Weight (kg)
28234	2 drums containment pallet (inline)	457 x 1245 x 635	1134	250	EPA, SPCC, U, O, UL	20
28703	3 drums containment pallet (inline)	295 x 1854 x 635	1701	284	EPA, SPCC, U, O, UL	26
28704	4 drums containment pallet (inline)	229 x 2464 x 635	2268	284	EPA, SPCC, U, O, UL	35
28254	4 drums containment pallet (in square)	260 x 1245 x 1245	2268	276	EPA, SPCC, U, O, UL	32
28923	4 drums accumulation center (in square)	140 x 1245 x 1245	2268	185	-	28
AK28905	8 drums accumulation center (inline)	140 x 2464 x 1245	4536	371	EPA, SPCC, U, O, UL	55
AK28906	Ramp for the centers	159 x 1219 x 838	455	-	-	19
28926	Joining clips (one pair - stainless steel)	-	-	-	-	0,1

<sup>(1)</sup> U : NFPA; O : OSHA

Flammable cabinets

Corrosive cabinets

Toxic cabinets and multirisk

Pesticide range

Fume hoods, filtering cabinets - Ventilation

Containment and Cans

Anti-fire equipments and Files cabinets

Showers and first-aid equipments